

SPECIFICATIONS

- Scepter L: 39.05" Height
- Steel base with aluminum body
- Input ratings: 120C AC 60Hz, 12A
- 10' 14 AWG x 3C Straight plug braided power cord
- (3) AC 120V Tamper-Resistant outlets
- (3) Qi wireless rapid chargers
- (2) USB Type-A DC 5V charging modules $(2 \times 2.4A + 2 \times 2.1A \text{ ports})$
- (1) 60W USB Type-C charging port
 (PD and QC enabled, up to 20V, 3A)

 \triangleright

(A)

- Wireless charging pockets with automatic alignment control
- Casters included
- Security slots and hardware included for permanent installation
- UL and cUL certified

							are	
POWER & LIGHTING SOLUTIONS www.MOD-PLS.com						REV		
						DATE		
						DRAWN		
1:10	SCALE	X. XX	××	[mm]	TOLERANCE (mm [INCH])	DRAWN APPROVED		
ф Д	VIEW		±2.5			DESCRIPTION		
mm[INCH] 1 OF 1	UNIT	X. XXX	X.X ±0.1	[INCH]				
1 OF 1	SHEET	±0.010	±0.1					
C-DK1600220318007 A	DRAWING# REV	PN	APPROVED	CHECKED	DRAWN			
		PN DOCK163216W-LLCB						
				JBX	YGY			
			DATE	DATE	DATE			
				JBX DATE Apr.11th 2023	YGY DATE Apr.11th 2023			
				23	23			