

power cord

Scepter T: 46.92" Height SPECIFICATIONS

Steel base with aluminum body Input ratings: 120C AC 60Hz, 12A

10' 14 AWG x 3C Straight plug braided

(3) AC 120V Tamper-Resistant outlets

(3) Qi wireless rapid chargers

USB Type-A DC 5V charging modules

 $x = 2.4A + 2 \times 2.1A \text{ ports}$

(PD and QC enabled, up to 20V, 3A) Wireless charging pockets with 60W USB Type-C charging port

automatic alignment control Casters included

included for permanent installation Security slots and hardware

UL and cUL certified

POWER & LIGHTING SOLUTIONS www.MOD-PLS.com						REV	
						DATE	
SHTING LS.com						DRAWN APPROVED	
1	,					APF	
1:10	SCALE	X. XX	××	a]		ROVED	
ф Д	VIEW	±0.25	# #2.5 #0.8	[mm]	TOLERANCE (mm [INCH])	DESCRIPTION	
mm[INCH] 1 OF 1	UNIT	X XXX	X.X ±0.1	[INCH]			
1 OF 1	SHEET	±0.010	±0.1	円			
C-DK1600220318008 A	DRAWING#	PN	APPI	DRAWN YGY CHECKED JBX	DRAWN		
		PN DOCK163216W-TLCB	APPROVED				
					YGY		
			DATE	DATE	YGY DATE		
				Apr.11th 2023	Apr.11th 2023		
				2023	2023		

 \bigcirc