



Specifications:

- * (6) Tamper-Resistant AC outlets
- * (2) USB Type-A charging ports: 1x2.4A and 1x2.1A
- * (1) USB Type-C charging ports: 60 watts Max. (PD and QC compatible with 20V,3A Max. Charging power)
- * (1) 5 VDC output for reading light (reserved for optional use)
- * (1) USB 3. X pass-through coupler
- * (1) RJ45 Ethernet pass-through coupler (POE compatible) 1
- * (1) 3.5mm Mic and headphone pass-through coupler
- * 6' 14AWG x 3c power cord
- * Rating: AC 125V 60Hz 15A
- * Compatible with National Lighting MA-02 series monitor arms supported with 0.98" (25 mm) outer-diameter mounting post. Max supported weight: 19.8 lbs (9.0kg) each arm
- * Mounting bracket is compatible with table top thickness up to 2.16"(55mm)
- * Over-current protection provided

REV	DATE	DRAWN	APPROVED	DESCRIPTION	SCALE	VIEW	UNIT	SHEET	REV
								1 OF 1	
				TOLERANCE (mm [INCH])	[mm]		[INCH]		
				X ±2.5	X	XX	±0.1		
				XX ±0.8	XX	XXX	±0.03		
				XXX ±0.25	XXX	XXXX	±0.010		
				SCALE	VIEW	UNIT	SHEET	DRAWING#	
				1:1		mm [INCH]	1 OF 1	C-DOCK1036200902-007	
				National Lighting®					
				www.nationallighting.com					
				TOLERANCE (mm [INCH])		[mm]		[INCH]	
				X ±2.5		X	±0.1	Sep 02nd 2020	
				XX ±0.8		XX	±0.03	Sep 02nd 2020	
				XXX ±0.25		XXX	±0.010		
				SCALE	VIEW	UNIT	SHEET	DRAWING#	
				1:1		mm [INCH]	1 OF 1	C-DOCK1036200902-007	
				National Lighting®					
				www.nationallighting.com					
				TOLERANCE (mm [INCH])		[mm]		[INCH]	
				X ±2.5		X	±0.1	Sep 02nd 2020	
				XX ±0.8		XX	±0.03	Sep 02nd 2020	
				XXX ±0.25		XXX	±0.010		
				SCALE	VIEW	UNIT	SHEET	DRAWING#	
				1:1		mm [INCH]	1 OF 1	C-DOCK1036200902-007	
				National Lighting®					
				www.nationallighting.com					