



INSTALLATION INSTRUCTIONS

Model: DOCK701-10000X-XX-12S-BK/ORB/WH/SA

Rating: AC 120V, 60Hz, 12A

Output: One 120V AC power outlet, One DC 5V 4.2A charger with 2 charging ports

CAUTION:

To prevent the risk of fire and electric shock, please be sure to read all instructions before installing or using this unit.


WARNING:

To reduce the risk of fire, electric shock or injury to persons

1. For indoor and dry location use only.
2. Do not use with extension cords.
3. Do not install this device if there is not at least 10 meters (30 feet) or more of wire between the electrical outlet and the electrical service panel.
4. Do not plug a device or devices into receptacles that exceed a total of 12A.
5. Do not open or attempt to open the unit for any reason.

MOUNTING:

1. Cut a 4.88" X 4.02" (124mm X 102mm) hole on the mounting surface.
2. Remove the adhesive tape and protection inserts from the sides of the unit.
3. Set the DOCK-700 unit into the hole.
4. Place the mounting brackets through the included thumb screws. Tighten the screws by hand or use 4 mm hex wrench to secure the DOCK-700 to the desktop. Do not over-tighten the screws.
5. Plug power cord to the nearest wall outlet. Make sure the wall outlet is properly grounded.



Please contact with National Lighting Corp. at (562) 921-0056 for assistance.